

Figure 1






Figure 2



09645403.082500

Figure 3



09645404 - 082500

Figure 4






Figure 5



09545401 062500

Figure 6



09645404 082500

Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13

00000000000000000000000000000000




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24




Figure 25




Figure 26




Figure 27




Figure 28




Figure 29




Figure 30

DOCUMENT - PROPOSED




Figure 31

00000000-0000-0000-0000-000000000000




Figure 32





Figure 33



09645401-032500

Figure 34




Figure 35

The diagram shows a table structure with six columns. Above the table, seven labels (3502, 3504, 3506, 3508, 3510, 3512, 3514) are positioned, each with a curved arrow pointing to a specific column. The columns are labeled as follows: IC chip number, User information, Information to check soundness, Content of service, Status of use, and Term of validity. The table has a header row and three data rows.

IC chip number	User information	Information to check soundness	Content of service	Status of use	Term of validity

Figure 36

DOCUMENT P002500




Figure 37




Figure 38




Figure 39




Figure 40




Figure 41

00000000000000000000000000000000




Figure 42

Service facility A

0925401-0382500

IC chip number	User information	Information to check soundness	Content of service	Status of use	Term of validity

Service facility B

0925401-0382500

IC chip number	User information	Information to check soundness	Content of service	Status of use	Term of validity

Figure 43




Figure 44




Figure 45




Figure 46

4602	4604	4606
IC chip number	Facility of service	

Figure 47

